

DIP-30 Internet Camera

Features:

- View and configurate through Browser
- Built in web Server
- 640*480 VGA 15F/S 320*480 SVGA 30F/S
- Single IP for upto 8 cameras
- Supports DDNS
- Allows 20 simultanous viewers
- Up-grading through internet
- Compact user friendly



Technical Parameter :

Image Sensor	1/4Inch VGACMOS Active-Pixel Digital
Video S/N Ratio	46dB
Lens	High Speed/Colour
FOCUS	Manual
White Balance	Auto/Manual
Responsivity	1.9V/lux-sec(550nm)
Interface	LAN RJ-45(CAT5)10/100Base-T WLAN IEEE 802.11b(11Mbps)
PictureResolution(Pixel)	ppPoE,DHCP,HTTP,DDNS,SMTP,FTP,NTP
Frame Rate (JPEG)	Compression 320*240,640*480 320*240 30fps 640*480 15fps
Password Protection	3-level passwords(admin/user/guest)
Multi-users	Up to20 Simultaneous users
Web Browser Plug-in	Active X Plug-in for IE5.0 or above, Java Applet plug-in for Netscape 6.0 or above
Email	Picture and status
NTP(Netork Time Protocol)	Calibrate time clock from an Internet Time Server
Configurate/View Through	Web Browser
Power Requirement	DC5V 1.0 Amp (Max.)
Dimensions (Without Antenna)	Main Body 4 0mm(H) X 55mm(W) X 105mm(D) Main Body affixed with Stand 70mm(H) X 70mm(W) X 105mm(D)

The information contained herein is believed to be correct, but no guarantee for accuracy, completeness • DSW Electronics Ltd. reseves the right to make changes without notification.